



CableFree Solutions Limited
Holly House, St Clare Business Park,
Holly Road, Hampton Hill, Middlesex TW12 1QQ
T: +44 (020) 8941 7975 E : info@cablefreesolutions.com
F: +44 (020) 8941 2410 W: www.cablefreesolutions.com

CableFree Integrated Client Radio – Product Overview

System Features

- Pre-WiMax OFDM Radio Solution
- Integrated Client Radio (ICR) ideal as CPE
- Raw data rates up to 108Mbps
- Versions for either 2.3-2.5 or 5.1-5.8GHz ISM band
- Optional 5.4GHz band support
- Range up to 15km*
- Data Throughput up to 10Mbps (and 30Mbps**)
- Carrier-class OS with NAT, filtering, full management features
- Power-over-Ethernet technology
- No RF cables – single Cat 5 carries power + network data
- Rugged environmental IP66 waterproof enclosure

*Depends on radio environment and choice of base-station antennas
** Only with 266MHz CPU option



Applications

- Ideal CPE for Wireless ISP deployments
- Point-to-Point or Point-to-Multipoint Data network segments
- Wireless ISP
- Fast Roll-out & Temporary Deployment

Accessories

Mounting Brackets Wall, Pole, Tower or Tripod mount options available
Alignment kit Display of Local & Remote signal levels*
Management Suite Full range of solutions including SNMP, LinkManager™, AlarmView™, ClusterManager™

Embedded Router Platform

CableFree broadband radios are not cheap enterprise-grade WLAN components. They embody powerful carrier-class routers with advanced features normally not found in wireless bridges or access points. Such features include:

175/266MHz CPU • IP Bridging • Layer3 IP Routing • Border Gateway Protocol (BGP) • Ethernet-over-IP (EoIP) interfaces • Virtual Router Redundancy Protocol (VRRP) • WISP & hotspot –specific features including Walled Garden, Cookies, RADIUS authentication, accounting, control of connection time • uplink and downlink bandwidth control on a per-user basis • DHCP Client and Server • Network Address Translation (NAT), supports TDD transmission

Enhanced Wireless Performance

CableFree Integrated Client radios offer major advantages over competing radio products. Examples are:

- Highly configurable – up to 2 radio cards – ‘mix and match’ 2.4 or 5.3/5.8GHz
- Software-selectable 5, 10, 20, 40MHz channel widths.
- OFDM and DSSS Software-defined radio – ‘state-of-the art’ radio using powerful DSP technology
- Optional proprietary ‘Nstreme’ wireless protocol - improves P2P and P2MP wireless links beyond the WiFi 802.11x standard through packet optimisation. No protocol/speed degradation for long link distances. Added security layer.
- Sophisticated RadioOS software platform



Specifications

System Variant	W2GICRO (2.4GHz) and W5GICRO (5.3/5.8GHz)
Performance	
Range	Up to 15km (depends on base station antennas)
Bandwidth	54Mbps (108Mbps Turbo mode)
Power Consumption	10W; 48V fed from Power-over-Ethernet injector; 115/230Vac; optional Uninterruptible Power Supply (UPS)
Operating Temperature	-20...+60 deg C
Wireless	
Frequency	2.4GHz: 2.412-2.472 (5 MHz step, channels 1-13), 2484 (channel 14) 2.512-2.732 (20 MHz step, channels 15-26) - optional license required 5GHz: 5.150-5.350 (5 MHz step) 5.725-5.825 (5 MHz step) 5.47-5.725 GHz - optional license required. Please contact CableFree for further details.
Radio Type	Direct Sequence Spread Spectrum (DSSS)
Modulation	2.4GHz: CCK (11, 5.5Mbps), DQPSK (2Mbps), DBPSK (1Mbps); OFDM for data rate >20 Mbps 5GHz: OFDM (BPSK, QPSK, 16-QAM, 64-QAM)
Operation Channels	13
RF Output Power	18dBm (125mW) – under software control
Sensitivity @FER=0.08:	54 Mbps OFDM -73 dBm; 48 Mbps OFDM -76 dBm; 36 Mbps OFDM -82 dBm; 24 Mbps OFDM -85 dBm; 18 Mbps OFDM -88 dBm; 12 Mbps OFDM -89 dBm; 11 Mbps OFDM -91 dBm; 9 Mbps OFDM -90 dBm; 6 Mbps OFDM -91 dBm; 5.5Mbps OFDM -92 dBm; 2 Mbps OFDM -93 dBm; 1 Mbps OFDM -94 dBm
Radio Data Rate	2.4GHz-b: 11, 5.5, 2, 1 Mbps, auto-fallback 2.4GHz-g (Normal mode): 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps, auto-fallback 2.4GHz-g (Turbo mode): 108,96,72,48,36,24,18,12 Mbps, auto-fallback 5GHz (Normal mode): 54, 48, 36, 24, 18, 12, 9, 6 Mbps, auto-fallback 5GHz (Turbo mode): 108, 96, 72 48, 36, 24, 18, 12 Mbps, auto-fallback
Compatibility	Proprietary modes plus back compatibility fully interoperable with IEEE 802.11b compliant products
Radio Architecture	Support ad-hoc, peer-to-peer networks and infrastructure communication to wired Ethernet networks via Access Point
Security	64/128-bit WEP data encryption; WPA; Proprietary mode
Integrated Antenna	
Specifications	2.4GHz: 2.4-2.7 GHz, 17dBi, VSWR 1.5:1, Linear H/V Polarisation, 20degree beamwidth, 10W power handling. 5GHz: 5.15-5.875 GHz, 23dBi, VSWR 1.5:1, Linear H/V Polarisation, 10.5degree beamwidth, 24dB cross-polarisation, 10W power handling, 35dB Front-to-Back ratio. 15 Degree Coverage Version Available On Request
Router Platform	
CPU	AMD x86-class 133MHz or 266MHz; 8MB SRAM; 64MB FLASH
System Software	RadioOS 8.1; Choice of license levels 1-6; Remotely Upgradeable via TFTP, features bandwidth control, authentication, NAT, routing
Management	Local and Remote configuration, control and administration via RS232, Telnet, HTTP, SNMP and Proprietary protocols
Mechanical	
Dimensions (mm)	305x305x15mm (diamond shape)
Connectors	Internal: RS232 console: DB9 External: 10/100 Ethernet with auto MDI/MDIX: Waterproof RJ45
Environmental	IP66
Weight	3kg

Product Code	Description
W2GICRO	2.4GHz radio, IP65-rated outdoor unit with integrated 17dBi 2.4GHz Antenna, pre-loaded software, Power-over-Ethernet injector with mains 115/230Vac input, not including Ethernet cable.
W5GICRO	5.3/5.8GHz radio, IP65-rated outdoor unit with integrated 23dBi 2.4GHz Antenna, pre-loaded software, Power-over-Ethernet injector with mains 115/230Vac input. not including Ethernet cable.